

ЕКГ

Технически спецификации

- ◆ 1.77" colorTFT-LCD.
- ◆ Quickly to check ECG once finger touching, convenient to operate.
- ◆ Accurate conclusion can be obtained immediately after measuring.
- ◆ The built-in rechargeable lithium battery can continuously record for up to 500 cases in full charging.
- ◆ Bluetooth transmission.
- ◆ ECG data can be saved to CLOUD Platform permanently, convenient to check and analyze.
- ◆ Historical data can be printed at any time, convenient to diagnose.
- ◆ Calibration voltage: $1\text{ mV} \pm 5\%$
- ◆ Standard sensitivity: $10\text{ mm/mV} \pm 5\%$
- ◆ Amplitude frequency characteristic: standard: 10 Hz , $1\text{ Hz} \sim 20\text{ Hz}$; (+0.4dB, -3dB)
- ◆ Noise level: $30\mu\text{V}$
- ◆ CMRR: $\infty, 60\text{ dB}$
- ◆ Scanning speed: $25\text{ mm/s} \pm 5\%$
- ◆ Sampling rate: 250 dots/s
- ◆ HR measurement range: $30\text{ bpm} \sim 300\text{ bpm}$, error: $\pm 1\text{ bpm}$ or 1%
- ◆ Type of protection against electric shock: Internal power device
- ◆ Degree of protection against electric shock: Type BF applied part
- ◆ Degree of waterproof: IP22